



L Type

S Type

• MATERIALS:(RoHS Compliant)

Housing And Cover: Plastic Thermoplastic
P.B.T UL94V-0 Black
Contacts: Phosphor Bronze Gold
Selective Plated
Bracket: Zinc Alloy Nickel
Plated Over Copper

• ELECTRICAL CHARACTERISTICS:

Contact Current Rating: 1 Amp
Dielectric Withstanding Voltage: 500V AC
Insulation Resistance: >500MΩ/Min
Contact Resistance: 35mΩ/Max
Operation Temperature: -55°C ~ +105°C

Ordering Code:

HPCNS

-

26

-

F

-

L

-

3

-

3

- ① Series No:

② Contact NO. :
26=26P

③ Contact Type:
F:Female
- ④ BRACKET FINISHES:
L=Latch Bracket
S=Screw Bracket

⑤ THREADED FINISHES:
1: #2-56
2: #4-40
3: M2.6

⑥ Contact Plating:
1: Gold Flash Selective Plating
3: 5u" Gold Selective Plating
5: 15u" Gold Selective Plating
7: 30u" Gold Selective Plating

Unless Otherwise specified tolerance		 ANTENK ELECTRONICS CO.,LTD Http://www.antenk.com E-mail:sales@antenk.com
X. ± 0.35 X.XX: ± 0.20 X.X: ± 0.25 X.XXX: ± 0.15		
SCALE: As Shown	UNIT: mm	
DRAW Jack Bao	DATE 9/25/2018	
CHECK Bob Yang	DATE 9/25/2018	TITLE:1.27mm Series 26P Cable Receptacle Connector Solder Molded Ribbon Type
 3rd ANGLE PROJECTION		DRAWING NO: HPCNS-26FL33
		PRODUCT NO: HPCNS-26FL33

REV	DESCRIPTION	DATE
1		
2		
3		
4		
5		